WEIGHT CLASS 6.5 TONNE TCR50-2







Japanese for Reliability



New TCR50-2 Tracked Dumper with left & right skip-tipping

The new TCR50-2 tracked dumper offers greater functionality, performance, comfort and serviceability.

With an ample 65-degree skip tip angle and 3,700kg maximum loading weight, operators' always get a maximum load discharged with a single operation.

The TCR50-2 features left and right skip-tip functionality (180 degree) offering efficient sideways dumping in restricted areas, this limits the need to continually reposition the machine.

























TRACKED DUMPER



ADDED SITE SAFETY

The new TCR50-2 is packed full of on-site safety features including 180 degree rear view colour camera with auto activation, operators can customise the camera settings.

Visibility is maximised with 3 rear view mirrors, LED work lights and tinted sun visor. The cab window has rear screen wash wipe function and window vents.

The pre-wired beacon switch and internal power socket come as standard. The customisable travel alarm has option for forward and reverse travel or only as reverse alarm.

Added safety on site for operators, with roof and cab glass guard fitted as standard and anti-slip walkways and steps.

A robust and heavy duty undercarriage, incorporating removable steel engine sump guard plates.

The 65 degree tilting skip comes with a skip body lock and 4 anchor points make for secure transporting.





ENGINE

- EU Stage V Turbocharged Yanmar Engine
- Automatic Fuel Bleed System
- DOC+DPF+SCR Exhaust After Treatment
- Double Element Air Cleaner
- Automatic Deceleration
- High Capacity Fuel Tank
- Engine Safety Start System on Left Console
- Engine Auto Stop
- Fuel Transfer Pump

UNDERCARRIAGE & FRAME

- Double Flanged Track Rollers
- 2-Speed Travel with Automatic Shift
- High Torque Planetary Final Drive
- 450 mm Rubber Crawlers

ELECTRICAL

- 5.7" Color Multi-Informational Display
- Sealed Rocker Switches
- 12 volt System with80 amp Alternator
- LED Lighting Forward Facing, Front and Rear Cab
- Travel Alarm
- Beacon Lamp Switch
- Rear View Monitor
- Air Conditioning
- Immobiliser
- Radio









TRACKED DUMPER











MAXIMUM ACCESS & EASY SERVICE

The TCR50-2 is designed for maximum easy servicing. Well positioned grip-steps and handle bars provide safe access to service areas at the top of the machine for daily routines with 500 hour service intervals.





















Well positioned full colour enhanced visual display unit - warning indicators, rpm, hour meter, fuel, battery charge, temperature, oil pressure and maintenance alerts. New brand familiar switch brigade.













TFM - TAKEUCHI FLEET MANAGEMENT


Takeuchi Fleet Management is designed to help you better manage your fleet and lower your overall operating costs.





PROTECT YOUR INVESTMENT

The TCR50-2 now comes with the TSS
Takeuchi Security System as standard.










For more information locally

call us direct, or contact:



Takeuchi Mfg (UK) Ltd, Unit E2B Kingsway Business Park, John Boyd Dunlop Drive, Rochdale, Lancashire OL16 4NG Tel: 01706 657 722 Fax: 01706 657 744

Southern Depot at 20 Colthrop Business Park Colthrop Lane, Thatcham, Newbury, Berks RG19 4NB Tel: 01635 877 196 Fax: 01635 877 195



TCR50-2

Standard UK Specification

ota i dai di Ci Cipolini dalori			
Engine			
Make	YANMAR		
Model	4TNV94FHT-NTBC		
Rated Output (kW)/rpm	88.4 kW / 2,500 min-1		
Displacement (ml)	3053		
Amount of CO2 emission* (kWh)	732		
Starter (V-kW)	12-3		
Alternator (V-kW)	12-0.96		
Battery (IEC 60095-1) (V-A.h)	12-90		
CCA (A)	795		

Operating Performance	
Operating Weight (kg)	6550
Dumped Body Capacity - Heaped (m³)	2.055
Struck (m³)	1.15
Maximum Loading Weight (kg)	3,700
Travel Speed: 1st (km/h	7.0
2nd	9.5
Gradeability	30°
Ground Pressure:	
Dump Body Full (kPa)	42.0
Dump Body Empty (kPa)	27.0

H	Hydraulic System		
P1	I.P2	Variable Displacement	
		Pump	
Flo	ow Rate	122.5m L/min	
Re	elief Pressure	34.5 MPa	

Fluid Capacities	
Engine Lubrication (I)	10.5
Cooling System (I)	18.5
Fuel Tank (I)	127.0
Hydraulic Reservoir Capacity (I)	44.0
Hydraulic System (I)	84.0
DEF Tank (I)	13.8

	Safety & Health	
	Vibration - Levels Hand / Arm Body	< 2.5 m/s ² < 0.5 m/s ²
	Noise Level - Sound Power Level	LWA 102 dB
	Slew Brake	Wet Friction Plate

All dimensions unless otherwise stated are in millimeters.

*: The amount of CO2 emission refers to the value obtained by testing the parent engine representing the engine type (engine family member) being used; it shall not guarantee the performance of the machine. 6/2020

> Takeuchi machines come with a 2 year/2000 hours warranty as standard. Warranty exceptions to 1 year: fuel injection systems, electrical components, paint work and emission control items.

In accordance with our established policy of constant improvement, we reserve the right to amend these specifications at any time without notice. Photographs shown may feature non-standard equipment

